



XP-370B/370bm

Thermal Barcode Printer

- Compact and space saving design
- Easy paper load with adjustable paper guide
- Printing speed up to 152mm per second
- Max 100mm label diameter, external amount
- and board option
- Thermal sensitive resistance, photoelectric sensor
black mark sensor
- USB+Serial+ethernet or USB+Serial or
USB+Bluetooth option

APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

XP-370B/370BM

Desktop Barcode Printer



Model	XP-370B/XP-370BM	
Mode	Label print mode	Receipt print mode
Printing Features		
Resolution	203 DPI	
Printing method	Direct Thermal	
Print speed	152 mm/s Max.	
Max.print width	Max. 76 mm	
Media		
Media type	Thermal paper/Thermal stickers paper	
Media width	20~82 mm	
Media roll diameter	Max.100 mm	
Performance Features		
Memory	DRAM:4M FLASH:4M	
Interfaces	USB+Serial/ USB+Serial+Lan (Optional : Bluetooth)	
Sensors	Print head temperature sensor / Cover open / Paper end / Gap	
Drawer port	1 ports (Pin 2 for cashdrawer)	
Fonts/Graphics/Symbologies		
Character sizes	Font 0 to Font8	
1D barcode	CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14	
2D bar code	PDF417、QR_CODE、DATMATRIX	
Emulaion	TSPL	ESC/POS
Physical Features		
Dimension	231*163*150.7mm(D×W×H)	
Weight	1.50 kg	
Reliability		
Print head life	100 km	
Software		
Driver	Windows	Windows/ Linux/ Mac/ Android
Power supply		
Input	DC 24V/2.5A	
Environmental Conditions		
Operation environment	5 ~ 45°C, Humidity:RH 20 ~ 80%	
Storage environment	-40 ~ 55 °C, Humidity: ≤93%RH(40°C)	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

